

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A fairing for mounting upon a cylindrical member for underwater deployment, the fairing comprising:

a fairing body which, viewed along its length, is substantially wedge-shaped, having a relatively broad front tapering to a relatively narrow trailing edge[.], and

at least two collars which are both secured to the fairing body and are separated from each other along the length of the fairing body, the collars being positioned and aligned to receive the cylindrical member with ~~the fairing body's front lying~~ a front face of the fairing body which lies adjacent the cylindrical member and the axis of the cylindrical member lying along the length of the fairing body, thereby to pivotally mount the fairing body upon the cylindrical member such that it is able to rotate about the axis of the cylindrical member and so align itself with a water current, the collars each comprising resiliently deformable material and a respective bearing ring having a gap so that the respective bearing ring can be opened out to enable the cylindrical member to be introduced into the bearing ring, the bearing rings being at opposite ends of the fairing body and each having a portion which extends beyond the adjacent front face of the fairing body to provide an exposed annular surface. ~~the fairing body and the cylindrical member together defining, when viewed along the length of the fairing, a~~

~~teardrop shape having a leading edge formed, between the collars, by the cylindrical member.~~

2. (Original) A fairing as claimed in claim 1 wherein a portion of each collar is interposed between the fairing body and the cylindrical member in use, providing clearance therebetween.
3. (Cancelled)
4. (Original) A fairing as claimed in claim 3 wherein each bearing ring has a substantially circular interior bearing surface.
5. (Cancelled)
6. (Original) A fairing as claimed in claim 5 wherein at least an end portion of the collar is initially free to allow the bearing ring to be opened out and means are provided to subsequently secure the free end of the collar to the fairing body to retain the fairing upon the cylindrical member.
7. (Original) A fairing as claimed in claim 6 wherein means to secure the free end of the collar comprise a mechanical fastener.
8. (Previously Presented) A fairing as claimed in claim 1 wherein the collar comprises two bifurcated portions, one limb of each extending between the cylindrical member and the fairing body to provide clearance therebetween and the other limb of each being secured in use to the fairing body.

9. (Previously Presented) A fairing as claimed in claim 1 wherein the front of the fairing body is shaped to complement the cylindrical member, its surface(s) lying upon a notional cylinder.
10. (Original) A fairing as claimed in claim 1 wherein a bearing surface of the collar, which faces toward the cylindrical member and upon which the collar rides, comprises low friction material.
11. (Original) A fairing as claimed in claim 10 wherein the bearing surface comprises self lubricating material.
12. (Original) A fairing as claimed in claim 11 wherein the collar comprises a plastics material with an admixture of a friction reducing agent.
13. (Previously Presented) A fairing as claimed in claim 1 wherein the collar comprises an anti-fouling agent.
14. (Previously Presented) A fairing as claimed in claim 1 wherein the collar comprises a plastics material with an admixture of an anti-fouling agent.
15. (Previously Presented) A fairing as claimed in claim 1 wherein the fairing body and the collar are formed by separate plastics mouldings.
16. (Previously Presented) A fairing as claimed in claim 1 wherein the fairing body is a hollow plastics moulding whose interior communicates with the exterior to permit equalisation of pressure.

17. (Previously Presented) A fairing as claimed in claim 1 which is substantially neutrally buoyant.

18. (Cancelled)